



Rapid &

UNIVERSAL

Universal Glue - Transparent

Rapid high performance hot melt glues liquefy when heated and quickly fill gaps and stick to the materials. They cool, harden and reach high bond strength in several seconds. They also allow to move assemblies immediately - open time - to eliminate clamps and reduce drying time – set time - .

Applications :

For a wide range of heavy-duty applications involving different types of material. The glue works ideally on various material and for all kind of bonding requiring a high glue output. Also good for applications where transparent glue is needed. To be used with EG280, 320 and any other tool from the PRO assortment.

Features & Sustainability :

Made of EVA basis.

Solvent free and non irritant.

Universal glue for all kind of bonding. Glue dries quick, helps to cover wider surfaces quickly, prevents from holding the parts too long.

Transparent rendering for invisible gluing.

Low viscosity for high flow rate which increase productivity.

High content for Installation use.

Long sticks for high efficiency, less reloading.

Box can be presented laid or hanged.

To strengthen Rapid sustainability policy, the carton packaging is FSC certified.

Storage :

Unlimited in standard ambient conditions: 15 to 35 °C. Store away from heat. Store in dry, dust-free, and well ventilated environment. Keep in cool and dark area.

Specifications:

- Diameter : 12mm
- Stick length : 190mm
- Colour : Transparent
- Softening point (Ring & Ball) : 80 96 °C
- Open time : ~ 20 seconds
- Set time : ~ 15 seconds
- Application range : 170 190 °C according to the type of applicator and used materials



Description	Packaging	Art. No	EAN	Inner/Outer
Glue D12 Univ. Transp.	Box	5001411	4051661034244	4pcs/12pcs

1. All data and recommendations are based on Rapid's research and experience but are provided as recommendations. It is the customer responsibility to validate that the result best meets his needs for a specific application. The customer is the only liable party in case of non Compliance or poor result.

The technical data refer to each product specifically and must not be applicable to other Rapid's products or to competitors' products.
Rapid's liability is restricted to supply of products according to product specifications.

ISABERG RAPID AB, BOX 115 SE-335 03 HESTRA, SWEDEN www.rapid.com



