



PRO-B Professional Hot Melt Adhesives

Rapid high performance hot melt glues liquefy when heated and quickly fill gaps and stick to the materials. They cool, harden and reach high bond strength in several seconds. They also allow to move assemblies immediately - open time - to eliminate clamps and reduce drying time – set time - .

Applications :

PRO-B glue for bonding a wide range of materials, such as: sanitary, cables, porous materials.

Features :

Made of EVA basis
High resin based which provides high strength.
High viscosity for flexibility on soft materials

Storage

Unlimited in standard ambient conditions: 15 à 35° C. Store away from heat. Store in dry, dust-free, and well ventilated environment. Keep in cool and dark area.

Specifications

- Diameter : 12mm
- Stick length : 190mm, 295mm
- Color : White
- Softening point (Ring & Ball) : 80-96°C
- Open time: ~ 30 second
- Set time: ~ 30 second
- Application range : 170 – 190 ° C according to the type of applicator and used materials



| Description | Packaging | Art. No | EAN | Inner/Outer |
|-----------------------------|-----------|----------|---------------|-------------|
| PRO-B glue 1kg | bag | 40302803 | 3221633028033 | 10 |
| PRO-B glue 2,5kg (lg.295mm) | bag | 40302804 | 3221633028040 | 4 |

1. All data and recommendations are based on Rapid's research and experience but are provided as recommendations. It is the customer responsibility to validate that the result best meets his needs for a specific application. The customer is the only liable party in case of non Compliance or poor result.
2. The technical data refer to each product specifically and must not be applicable to other Rapid's products or to competitors' products.
3. Rapid's liability is restricted to supply of products according to product specifications.



ISABERG RAPID AB, BOX 115, SE-330 27 HESTRA, SWEDEN
Tel + 46 (0)370 33 95 00. www.rapid.com

Rapid[®]
SVENSKEFFIXITY