



Glue for PVC, Cable and Plastics

Rapid high performance hot melt glues liquefy when heated and quickly fill gaps and stick to the materials. They cool, harden and reach high bond strength in several seconds. They also allow to move assemblies immediately - open time - to eliminate clamps and reduce drying time – set time - .

Applications :

For light-duty to medium-duty applications such as gluing cables of a new electronic device, bonding broken pieces of a toy together or repairing anything made of plastics or PVC... The glue works perfectly on glass, plexiglass and on rubber. To be used with EG212, CG270 and BGX300.

Features :

- Made of EVA basis.
- Solvent free and non irritant.
- High resin based which provides high strength.
- Plastics glue gives strong bond on the materials. Glue dries quick, helps to cover wider surfaces quickly, prevents from holding the parts too long.
- Transparent rendering for invisible gluing.
- Low viscosity for high flow rate which increase productivity.
- Packed in short and long PET blisters of 14 pcs each :
 - > Short sticks for easier switch to different speciality glues and better handling.
 - > Long sticks for higher efficiency, less reloading.

Storage :

Unlimited in standard ambient conditions: 15 to 35 °C. Store away from heat. Store in dry, dust-free, and well ventilated environment. Keep in cool and dark area.

Specifications :

- Diameter : 12mm
- Stick length : 190mm / 94mm
- Colour : Transparent
- Softening point (Ring & Ball) : 80 - 96 °C
- Open time : ~ 30 seconds
- Set time : ~ 30 seconds
- Application range : 170 - 190 °C according to the type of applicator and used materials



Description	Packaging	Art. No	EAN	Inner/Outer
Glue D12 PVC-Cable 14pcs*94mm West	Blister	40107358	3221631073585	10pcs/80pcs
Glue D12 PVC-Cable 14pcs*94mm East	Blister	5000695	4051661021534	10pcs/80pcs
Glue D12 PVC-Cable 14pcs*190mm	Blister	40107363	3221631073639	10pcs/40pcs

1. All data and recommendations are based on Rapid's research and experience but are provided as recommendations. It is the customer responsibility to validate that the result best meets his needs for a specific application. The customer is the only liable party in case of non Compliance or poor result.
 2. The technical data refer to each product specifically and must not be applicable to other Rapid's products or to competitors' products.
 3. Rapid's liability is restricted to supply of products according to product specifications.



**ISABERG RAPID AB, BOX 115
 SE-335 03 HESTRA, SWEDEN
 www.rapid.com**

