

MAXIPACK
48 PCS.



Glue for Wood and Derivates

Rapid high performance hot melt glues liquefy when heated and quickly fill gaps and stick to the materials. They cool, harden and reach high bond strength in several seconds. They also allow to move assemblies immediately - open time - to eliminate clamps and reduce drying time - set time - .

Applications :

For heavy-duty applications such as bonding wood floors, stairways, wall coverings or gluing large surfaces of wood and derivates, paper, cardboard... The glue also works perfectly on cork. To be used with EG280, 320 and any other tool from the PRO assortment.

Features & Sustainability :

Made of EVA basis.

Solvent free and non irritant.

High resin based which provides high strength.

Wood glue gives strong bond on the materials. Glue dries quick, helps to cover wider surfaces quickly, prevents from holding the parts too long.

Low viscosity for high flow rate which increase productivity.

High content for Installation use.

Longs sticks for high efficiency, less reloading.

Box can be presented laid or hanged.

To strengthen Rapid sustainability policy, the carton packaging is FSC certified.



Storage :

Unlimited in standard ambient conditions: 15 to 35 °C. Store away from heat.

Store in dry, dust-free, and well ventilated environment. Keep in cool and dark area.

Specifications :

- Diameter : 12mm
- Stick length : 190mm
- Colour : Yellow
- Softening point (Ring & Ball) : 80 - 96 °C
- Open time : ~ 30 seconds
- Set time : ~ 30 seconds
- Application range : 170 - 190 °C according to the type of applicator and used materials



Description

Glue D12 Wood & derivates

Packaging

Box

Art. No

5001421

EAN

4051661034343

Inner/Outer

4pcs/12pcs

1. All data and recommendations are based on Rapid's research and experience but are provided as recommendations. It is the customer responsibility to validate that the result best meets his needs for a specific application. The customer is the only liable party in case of non Compliance or poor result.
2. The technical data refer to each product specifically and must not be applicable to other Rapid's products or to competitors' products.
3. Rapid's liability is restricted to supply of products according to product specifications.

ISABERG RAPID AB, BOX 115
SE-335 03 HESTRA, SWEDEN
www.rapid.com

Rapid®
SVENSK EFFIXITY